

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
31 March 2005 (31.03.2005)

PCT

(10) International Publication Number
WO 2005/028930 A1

(51) International Patent Classification⁷: F16K 11/074, G05D 23/13

(21) International Application Number: PCT/NZ2004/000225

(22) International Filing Date: 21 September 2004 (21.09.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data: 528442 25 September 2003 (25.09.2003) NZ

(71) Applicant (for all designated States except US): GREENS INDUSTRIES LIMITED [NZ/NZ]; 279 Kahikatea Drive, Hamilton (NZ).

(72) Inventors; and

(75) Inventors/Applicants (for US only): GREEN, John, William [NZ/NZ]; Flat 6, 122 Firth Street, Hamilton East (NZ). MORAN, Ian [GB/NZ]; 20 Nixon Street, Hamilton (NZ).


(74) Agent: HARDIE, John, David; c/o J.D Hardie & Co., P.O. Box 1534, Auckland (NZ).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: TEMPERATURE LIMITING DEVICE APPLICABLE TO SINGLE LEVER VALVES FOR MIXING HOT AND COLD LIQUIDS



(57) Abstract: A single lever valve for mixing hot and cold liquids has a mixer which can internally impose and upper limit on the temperature of any liquid emerging from it. The means used may enable the upper limit to be changed by exchange of a component so that the mixer can be used in any location in an installation even though different locations might have different upper limit requirements. The mixer may take the form of a cartridge able to be exchanged with an existing cartridge to convert an "unsafe" mixer to a "safe" one.



ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— *with amended claims*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*